

轮片特点

轮面材料:	人造胶	轮芯材料:	高强度聚丙烯
轴 承:	单滚珠	胎面硬度:	85A±3
建议温度:	-15°C~60°C	运行速度:	3.2km/h

注意: 超出建议温度范围或超出建议速度使用, 可能会缩短产品使用寿命甚至损坏产品。

- ✔ 精密单轴承, 转动灵活
- ✔ 高级人造胶材质, 注塑粘合成型
- ✔ 软质轮面静音, 有效保护地面
- ✔ 凹凸设计防尘盖, 美观简洁













运行省力	■ ■ ■ □ □	一般
磨损寿命	■ ■ ■ □ □	一般
静音效果	■ ■ ■ ■ ■	优秀
地面保护	■ ■ ■ ■ ■	优秀




支架特点

- ✔ 刹车简洁省力, 可指压操作
- ✔ 刹车疲劳可达3000次以上
- ✔ 镀铬处理, 表面光亮美观
- ⚠ 单刹轮片, 不锁方向

外形尺寸 (mm)	 载重	 轮径	 轮宽	 全高	 偏心距 F	 旋转半径 r	 旋转半径 R
1"	10 kg	25	13	37.5	15.5	28	47.5
1.25"	15 kg	32	13	44.5	15	31	49
1.5"	20 kg	38	17	52	18.5	37.5	59.5
2"	25 kg	50	17	64	19	44	62.5




安装尺寸




平板方向/刹车

尺寸 D	轮径 D	底板尺寸 A×B	孔距 a×b	孔径 Φd
1"	25	39×33	30×24	4.3
1.25"	32	39×33	30×24	4.3
1.5"	38	46×39.5	36×28	4.3
2"	50	46×39.5	36×28	5.2



平板定向

尺寸 D	轮径 D	底板尺寸 A×B	孔距 a×b	孔径 Φd
1"	25	38×30	30×24	4.3
1.25"	32	39×33	30×24	4.3
1.5"	38	46×37.5	36×28	4.3
2"	50	46×38	36×28	5.2



丝杆

尺寸 D	轮径 D	丝杆 m×h
1"	25	M8×20
1.25"	32	M8×20
1.5"	38	M8×20
2"	50	M10×25

产品代码

产品图片




轮径	平板方向	平板定向	平板刹车	丝杆方向	丝杆刹车
1"	10B01-1510	10B02-1510	10B03-1510	10B04-1510	10B05-1510
1.25"	10B06-1511	10B07-1511	10B08-1511	10B09-1511	10B10-1511
1.5"	10B11-1512	10B12-1512	10B13-1512	10B14-1512	10B15-1512
2"	10B16-1513	10B17-1513	10B18-1513	10B19-1513	10B20-1513

产品特征



凹凸设计防尘盖，美观简洁

支架表面镀铬处理，光亮美观



双波盘转向设计，结构稳定，转动灵活

