

轮片特点

轮面材料:	尼龙	轮芯材料:	尼龙
轴 承:	无	胎面硬度:	75D±3
建议温度:	-30°C~90°C	运行速度:	4km/h

注意: 超出建议温度范围或超出建议速度使用, 可能会缩短产品使用寿命甚至损坏产品。

- ✔ 尼龙材质整体注塑成型, 高载, 耐磨
- ✔ 不易变形, 抗老化, 耐水解
- ⚠ 干磨轴, 转动灵活度低
- ⚠ 硬质轮面, 可能会造成地坪损伤
- ⚠ 运行有一定噪音






运行省力	■■■■■	优秀
磨损寿命	■■■■■	优秀
静音效果	■□□□	可接受
地面保护	■□□□	可接受





支架特点

- ✔ 铸铝一体成型, 轻便坚固结实
- ✔ 支撑座通过旋钮调节, 固定效果出色
- ✔ 喷塑处理, 美观更环保, 防腐性能更好

外形尺寸 (mm)	 载重	 轮径	 轮宽	 全高	 偏心距 F	 旋转半径 r
1.5"	50 kg	65	19	73.5	30.5	50.5
2"	250 kg	75	24	86	38	63
2.5"	500 kg	100	30	106.5	44	75
3"	750 kg	100	31	120	52.5	90
4"	1000 kg	100	31	120	52.5	90



## 安装尺寸



尺寸 D	轮径 D	底板尺寸 A x B	安装孔距 a x b	孔径 Φd	孔顶 Φd
1.5	40	55.5×55.5	42×42	6.6	M10
2	50	73.5×73.5	58×58	7	M12
2.5	62	90×90	70×70	9	M14
3	75	95×95	70×70	10.8	M14
3	75	95×95	70×70	10.8	M14

## 产品代码

## 产品图片



## 轮径

平板万向

顶孔万向

1.5"

32A01-1611

32A07-1611

2"

32A02-1612

32A08-1612

2.5"

32A03-1613

32A09-1613

3"

32A04-1614

32A10-1614

4"

32A05-1614

32A11-1614

## 产品特征

支架整体铸铝成型，轻便坚固结实。



旋钮调节，可升降调节支撑座，固定轻松便捷。



轮片尼龙整体注塑成型，承载高，抗老化。



喷塑处理，美观更环保，防腐性能好。



[中文简体]

